




### **Model 100 & 200**

The Series 100 & 200 offers a cost-effective, field-hardened solution with minimal upkeep and high analytical precision, favored in applications where accurate, real-time H<sub>2</sub>S monitoring is mission-critical.

### **Applications**

- Gas Processing Facilities
- Natural Gas Pipelines
- Refineries
- Biogas
- Landfills
- Chemical Plants
- Liquid Petroleum Gas (LPG)
- Liquid Natural Gas (LNG)
- Environmental



### **Benefits**

- No false positives ever
- Automatic self-zero
- Fast response time
- Quantitative measurement in PPB, PPM & percent levels
- Proven reliability
- Conformity to ASTM methods

### **Operational Impact**

- High accuracy and wide range
- Low maintenance
- Calibration stability
- Low cost of ownership
- Continuous analysis
- Explosion-proof design (200)



Scan to know  
more about  
KECO Model 100  
& 200



## **Specifications**

### **DISPLAY**

- Alpha Numeric LCD
- 128 x 64 pixel
- Back-lit display (optional)
- LCD Graph Display w/ month of data (optional)

### **TEMPERATURE RANGES**

- 1°C to 50°C (operating) without cooling/heating
- 0°C to 70°C (storage)

### **ANALOG**

- 4-20mA Isolated

### **ANALYTICAL PERFORMANCE**

- Resolution: 1 ppb
- Accuracy:  $\pm 2\%$  of FS
- Repeatability:  $\pm 1\%$  of FS
- Linearity:  $\pm 1\%$  of FS
- Drift: Nil
- Temp. Coefficient: 0.01% / °C
- Analysis time: 0.75 Second (continuous)

### **DETECTION RANGES**

- 0-1 ppm by vol.
- 0-10 ppm by vol.
- 0-50 ppm by vol.
- 0-100 ppm by vol.
- 0-500 ppm by vol.
- Up to 100%
- Customer specified (contact factory)

### **SAMPLING SYSTEM (STANDARD)**

- Sample Pressure Regulator
- Sample Flow Meter
- Secondary particulate filter
- Fast sweep (fast loop) needle valve

### **ENCLOSURE (CABINET)**

- High-impact, industrial strength fiberglass
- NEMA 4X / IP 65 options
- Stainless Steel options available

### **WEIGHT/DIMENSIONS**

- 50 lbs. w/o options (Series 200)
- 20 lbs. w/o options (Series 100)
- 17" W X 19" H X 10" D (Series 200)
- 14" W X 16" H X 8" D (Series 100)

### **UTILITIES/SETTINGS**

- 12VDC, 24VDC, 110VAC or 220VAC
- 5 Watts (without heater option) 10 Watts max
- Carrier Air: (for 501+ ppm ranges only) 130 ml/min
- Sample flow: 0.3 SCFH
- Sample pressure: 10 psig constant
- Calibration gas: H<sub>2</sub>S ~25% of scale balance N<sub>2</sub>, 2L per cal

### **AREA CLASSIFICATIONS**

- Class 1 Division 1 (Series 200)
- Class 1 Division 2 (Series 200)
- Zone 1 or Zone 2 (Series 200) General purpose/non-explosion proof (Series 100)

### **AVAILABLE OPTIONS**

- Concentration relay alarms
- Diagnostic/fault relay alarms
- Low flow relay alarms
- RS-232/485 Modbus
- Data Logger for data download to PC
- Remote monitoring/control with PC
- TCP IP Ethernet
- Automatic calibration
- H<sub>2</sub>S Scrubber (for vent)
- Cabinet heater & thermostat
- Fugitive Emission Control Unit (for vent)
- Hazardous area certificates may be available (added cost)
- Sample Probe
- Sampling System for gas contaminated with liquids
- Sampling System for LNG/LPG (Vaporizing Regulator)

KECO provides design and application engineering assistance for the User's analyzer requirements. For a quotation, please complete Analyzer Quote Request Form at [kecosystems.com/quote](https://kecosystems.com/quote)

KECO reserves the right to make revisions and or changes without notice. KECO shall not be liable for any errors or omissions made or any damages resulting from the use of the analyzer, information, or the manual. © 2025 Printed in the USA.